

PVC Mesh OM1012



Company Address
 Room 1203 No.889 Zhong Jiang Road,
 Pu Tuo District Shang Hai, China
 Zip: 200333
 Tel: +86-21-52839201
 Fax: +86-21-52839200
 Email: info@osign.com.cn

Item	Data	Unit	Method
Yarn	1000 x 1000	Denier	DIN60001
Net structure	12 x 12	Thread / Inch	DIN53853
Net weight	110	g/sq.m	DIN53352
PVC coated	160	g/sq.m	DIN53352
Product weight	270	g/sq.m	DIN53352
Thickness	-----	mm	DIN53353
Products width	0.914 ~ 5.00	m	-----
Tearing strength	L 280	N/5cm	DIN53363
	W 280		
Tensile strength	L 1100	N/5cm	DIN53354
	W 1100		
Elongation value	L 26	%	DIN53354
	W 26		
Peeling strength	1017	N/5cm	DIN53357
Light transmission	-----	%	ASTM D 1003
Temperature	-30℃ ~ +70℃	℃	DIN53372
Expired time	6 ~ 12 months		-----
Flame retardant	pass		DIN75200
Anti-wicking	without		-----
Anti-frost	without		-----
Anti-mildew	without		-----
Acrylic lacquer	without		-----
Applications	<p>OSIGN OM1012 Mesh is a special inkjet media and an open weave flexible sign face materials. It featured by whiteness color, regular net structure, softness feeling high tear strength and excellent printing effect. Our mesh is ideal outdoor printing material for building wrap cover billboard banner, window curtain advertisement and other usage.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA TECKWIN, FLORA, INFINITI, etc</p>		

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).