

Digital Inkjet Printing Media

Add: Room 1203, CaoYang Business Tower, No.889 ZhongJiang Road, Putuo District, Shanghai City, China 200333 Tel:+86-21-52839201/2/3 Fax:+86-21-5283920

E-mail: Info@osign.com.cn Web Site: www.osign.com.cn

Coated Backlit Banner OB1018/15oz







Item	Da	Data		Method
Yarn	1000	1000 x 1000		DIN60001
Net structure	18	18x18		DIN53853
Net weight	1	180		DIN53352
PVC film weight	3	330		DIN53352
Product weight	510	510 (±15)		DIN53352
Thickness	0.42 (0.42 (±0.02)		DIN53353
Products width	0.914	0.914 ~ 5.00		~~~
Tearing strength	L	380	N/5cm DIN53363	
	W	380		
Tensile strength	L	2100	N/5cm	DIN53354
	W	2100		
Elongation Value	L	12	%	DIN53354
	W	12		
Peeling Strength	9	91		DIN53357
Lighting Transmission		8		ASTM D 1003
Temperature	-30℃~	-30℃~ +70℃		DIN53372
Expired time		6 ~ 12 months		~~~
Flame retardant		pass		
Anti-wicking	without			~~~
Anti-frost	without			~~~
Anti-mildew	without			~~~
Acrylic lacquer		without		
Applications	OSIGN OB1018/15oz Coated Back-lit flex are durable ,translucent, banner outdoor signs usage, include street light box display, City light billboard, Store Cabinets and others. Its excellent printability allows a vey clear and vivid image on the billboard. It's featured by its high physical performance in peel, tensile and tear strength. This high quality back-lit flex even can be use in extreme cold/hot or windy outdoor conditions. It optimized for solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR,HP SCITEX, EPSON, DGI, ROLAND, MUTOH,MIMAKI,			

ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, ETC.

Durability

Durability is based on field experience and exposure tests in China.

Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20 $^{\circ}\text{C}\ x$ 50% R.H.).