

## PVC Blockout Banner Ok1018/20oz



Item	Data	Unit	Method	
Yarn	1000 x 1000	Denier	DIN60001	
Net structure	18 x 18	Thread / Inch	DIN53853	
Net weight	180	g/sq.m	DIN53352	
PVC film weight	500	g/sq.m	DIN53352	
Product weight	680 (±20)	g/sq.m	DIN53352	
Thickness	0.56 (±0.02)	mm	DIN53353	
Products width	0.914 ~ 5.00	m	-----	
Tearing strength	L	380	N/5cm	DIN53363
	W	380		
Tensile strength	L	2100	N/5cm	DIN53354
	W	2100		
Elongation value	L	12	%	DIN53354
	W	12		
Peeling strength	91	N/5cm	DIN53357	
Light transmission	0	%	ASTM D 1003	
Temperature	-30°C ~ +70°C	°C	DIN53372	
Expired time	12 ~ 24	months	-----	
Flame retardant	pass		DIN75200	
Anti-wicking	without		-----	
Anti-frost	without		-----	
Anti-mildew	without		-----	
Acrylic lacquer	without		-----	

**Applications**

OSIGN OK1018/20oz is a smooth, scrim-reinforced construction and heavy banner that can be printable on both sides. It features a built-in black layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, roll up display, street banner, and other applications.

**Durability**

It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA.

**Durability is based on field experience and exposure tests in China.**

**Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).**

### Shelf Life

Shelf life is 1 year from factory shipment.

### Storage condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).

Company Address  
Room 1203 No.889 Zhong Jiang Road,  
Pu Tuo District Shang Hai, China  
Zip: 200333  
Tel: +86-21-52839201  
Fax: +86-21-52839200  
Email: info@osign.com.cn