

PVC Blockout Banner
Ok1100/13oz
black back



Item	Data	Unit	Method	
Yarn	1000 x 1000	Denier	DIN60001	
Net structure	9 x 9	Thread / Inch	DIN53853	
Net weight	80	g/sq.m	DIN53352	
PVC film weight	530	g/sq.m	DIN53352	
Product weight	610 (±20)	g/sq.m	DIN53352	
Thickness	0.52 (±0.02)	mm	DIN53353	
Products width	0.914 ~ 5.00	m	-----	
Tearing strength	L	270	N/5cm	DIN53363
	W	270		
Tensile strength	L	1350	N/5cm	DIN53354
	W	1350		
Elongation value	L	15	%	DIN53354
	W	16		
Peeling strength	36	N/5cm	DIN53357	
Light transmission	0	%	ASTM D 1003	
Temperature	-30°C ~ +70°C	°C	DIN53372	
Expired time	6 ~ 12 months		-----	
Flame retardant	pass		DIN75200	
Anti-wicking	without		-----	
Anti-frost	without		-----	
Anti-mildew	without		-----	
Acrylic lacquer	without		-----	
Applications	<p>OSIGN OK1100/13oz is a high tearing strength construction flex banner. It features a black (or grey) back layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, large format billboard, roll up display, street banner, and other applications.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc</p>			

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).

Company Address
 Room 1203 No.889 Zhong Jiang Road,
 Pu Tuo District Shang Hai, China
 Zip: 200333
 Tel: +86-21-52839201
 Fax: +86-21-52839200
 Email: info@osign.com.cn