

PVC Blockout Banner Ok1100/18oz



Company Address
 Room 1203 No.889 Zhong Jiang Road,
 Pu Tuo District Shang Hai, China
 Zip: 200333
 Tel: +86-21-52839201
 Fax: +86-21-52839200
 Email: info@osign.com.cn

Item	Data		Unit	Method
Yarn	1000 x 1000		Denier	DIN60001
Net structure	9 x 9		Thread / Inch	DIN53853
Net weight	80		g/sq.m	DIN53352
PVC film weight	530		g/sq.m	DIN53352
Product weight	610 (±20)		g/sq.m	DIN53352
Thickness	0.52 (±0.02)		mm	DIN53353
Products width	0.914 ~ 5.00		m	-----
Tearing strength	L	270	N/5cm	DIN53363
	W	270		
Tensile strength	L	1350	N/5cm	DIN53354
	W	1350		
Elongation value	L	15	%	DIN53354
	W	16		
Peeling strength	36		N/5cm	DIN53357
Light transmission	0		%	ASTM D 1003
Temperature	-30°C ~ +70°C		°C	DIN53372
Expired time	6 ~ 12 months			-----
Flame retardant	pass			DIN75200
Anti-wicking	without			-----
Anti-frost	without			-----
Anti-mildew	without			-----
Acrylic lacquer	without			-----
Applications	<p>OSIGN OK1100/18oz is a smooth, scrim-reinforced construction that can be printable on both sides. It features a built-in black layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, roll up display, street banner, and other applications.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA,</p>			

Durability
 Durability is based on field experience and exposure tests in China. Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life
 Shelf life is 1 year from factory shipment.

Storage condition
 Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).