

PVC Blockout Banner OK250/13oz



Company Address
Room 1203 No.889 Zhong Jiang Road,
Pu Tuo District Shang Hai, China
Zip: 200333
Tel: +86-21-52839201
Fax: +86-21-52839200
Email: info@osign.com.cn

Item	Data	Unit	Method
Yarn	250 x 250	Denier	DIN60001
Net structure	41 x 40	Thread / Inch	DIN53853
Net weight	180	g/sq.m	DIN53352
PVC film weight	260	g/sq.m	DIN53352
Product weight	440 (±10)	g/sq.m	DIN53352
Thickness	0.36 (±0.02)	mm	DIN53353
Products width	0.914 ~ 3.20	m	-----
Tearing strength	L 170	N/5cm	DIN53363
	W 170		
Tensile strength	L 520	N/5cm	DIN53354
	W 520		
Elongation value	L 17	%	DIN53354
	W 17		
Peeling strength	38	N/5cm	DIN53357
Light transmission	0	%	ASTM D 1003
Temperature	-30℃ ~ +70℃	℃	DIN53372
Expired time	6 ~ 12 months		-----
Flame retardant	pass		DIN75200
Anti-wicking	without		-----
Anti-frost	without		-----
Anti-mildew	without		-----
Acrylic lacquer	without		-----
Applications	<p>OSIGN OK250/13oz is a smooth, scrim-reinforced construction that is printable on both sides. It features a built-in black layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, roll up display, street banner, and other applications.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA,</p>		

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20℃ x 50% R.H.).