

PVC Blockout Banner
OK320/10oz
greyback



Company Address
Room 1203 No.889 Zhong Jiang Road,
Pu Tuo District Shang Hai, China
Zip: 200333
Tel: +86-21-52839201
Fax: +86-21-52839200
Email: info@osign.com.cn

Item	Data		Unit	Method
Yarn	300 x 200		Denier	DIN60001
Net structure	18 x 12		Thread / Inch	DIN53853
Net weight	40		g/sq.m	DIN53352
PVC film weight	300		g/sq.m	DIN53352
Product weight	340 (±10)		g/sq.m	DIN53352
Thickness	0.32 (±0.02)		mm	DIN53353
Products width	0.914 ~ 5.00		m	-----
Tearing strength	L	180	N/5cm	DIN53363
	W	200		
Tensile strength	L	350	N/5cm	DIN53354
	W	420		
Elongation value	L	12	%	DIN53354
	W	13		
Peeling strength	36		N/5cm	DIN53357
Light transmission	0		%	ASTM D 1003
Temperature	-30℃ ~ +70℃		℃	DIN53372
Expired time	6 ~ 12 months			-----
Flame retardant	pass			DIN75200
Anti-wicking	without			-----
Anti-frost	without			-----
Anti-mildew	without			-----
Acrylic lacquer	without			-----
Applications	OSIGN OK320/10oz is a high tearing strength construction flex banner. It features a grey (or black) back layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, large format billboard, roll up display, street banner, and other applications.			
	It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc			

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 years when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20°C x 50% R.H.).