

PVC Blockout Banner OK550/13oz blackback



Item	Data	Unit	Method	
Yarn	500 x 500	Denier	DIN60001	
Net structure	9 x 9	Thread / Inch	DIN53853	
Net weight	50	g/sq.m	DIN53352	
PVC film weight	390	g/sq.m	DIN53352	
Product weight	440 (±10)	g/sq.m	DIN53352	
Thickness	0.37 (±0.02)	mm	DIN53353	
Products width	0.914 ~ 5.00	m	-----	
Tearing strength	L	240	N/5cm	DIN53363
	W	240		
Tensile strength	L	800	N/5cm	DIN53354
	W	800		
Elongation value	L	15	%	DIN53354
	W	15		
Peeling strength	37	N/5cm	DIN53357	
Light transmission	15	%	ASTM D 1003	
Temperature	-30℃ ~ +70℃	℃	DIN53372	
Expired time	6 ~ 12 months		-----	
Flame retardant	pass		DIN75200	
Anti-wicking	without		-----	
Anti-frost	without		-----	
Anti-mildew	without		-----	
Acrylic lacquer	without		-----	
Applications	<p>OSIGN OK550/13oz is a high tearing strength construction flex banner. It features a black (or grey) back layer that prevents images from showing through to the other side. This product is designed for inkjet printing and screen printing for indoor and outdoor display banner, large format billboard, roll up display, street banner, and other applications.</p> <p>It optimized for Solvent, Eco-solvent, UV curable inkjet printer, such as VUTEK, NUR, HP SCITEX, EPSON, DGI, ROLAND, MUTOH, MIMAKI, ARIZONA, SALASA, TECKWIN, FLORA, INFINITI, etc</p>			

Durability

Durability is based on field experience and exposure tests in China. Outdoor durability is 1 year when properly processed and applied (unprinted film vertical exposure).

Shelf Life

Shelf life is 1 year from factory shipment.

Storage condition

Free from excessive moisture, temperature, direct sunlight (20℃ x 50% R.H.).

Company Address
Room 1203 No.889 Zhong Jiang Road,
Pu Tuo District Shang Hai, China
Zip: 200333
Tel: +86-21-52839201
Fax: +86-21-52839200
Email: info@osign.com.cn